



# Certificate of Compliance

**Certificate:** 1486277

**Master Contract:** 163017

**Project:** 1486277

**Date Issued:** 2004/11/12

**Issued to:** **Data Retrieval Corporation**  
13231 Champions Forest Dr, 401  
Houston, Texas 77069  
USA  
Attention: Nathan Waldman

*The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US'*



**Issued by:** Patrick Conway C.E.T.

**Authorized by:** Patricia Pasemko, Operations Manager

## **PRODUCTS**

**CLASS 2258 83** - PROCESS CONTROL EQUIPMENT-Intrinsically Safe and Non-Incendive - Systems-For Hazardous Locations-Certified to U.S. Standards

**CLASS 2258 03** - PROCESS CONTROL EQUIPMENT - Intrinsically Safe and Non Incendive Systems - For Hazardous

Class I, Groups A, B, C and D; Class II, Groups E, F, and G; Class III; AEx ia IIC T3; Type 4 enclosure.

Data Acquisition System model SPIDR EM, Rated at 4.5V dc, MWP 15000 psi. Temperature code T3. Intrinsically safe when powered by three (3) Eveready "Energizer" D cell alkaline battery P/N E95. Suitable for use in an ambient temperature range of -25°C to +85°C.

## **APPLICABLE REQUIREMENTS**

C22.2 No. 25-1966 - Enclosures for Use in Class II, Groups E, F and G Hazardous Locations

The 'C' and 'US' indicators adjacent to the CSA Mark signify that the product has been evaluated to the applicable CSA and ANSI/UL Standards, for use in Canada and the U.S., respectively. This 'US' indicator includes products eligible to bear the 'NRTL' indicator. NRTL, i.e. National Recognized Testing Laboratory, is a designation granted by the U.S. Occupational Safety and Health Administration (OSHA) to laboratories which have been recognized to perform certification to U.S. Standards.